SAFETY DATA SHEET

DEFENSE PAK FABRIC PROTECTOR

Infosafe No.: 1JBA2 Issued Date: 07/12/2016 Issued by: MotorOne Group Pty Ltd

1. IDENTIFICATION

GHS Product Identifier DEFENSE PAK FABRIC PROTECTOR

Company Name MotorOne Group Pty Ltd

Address 275 Canterbury Road Canterbury VIC 3126 Australia

Telephone/Fax Number Tel: (03) 8809 2700 Fax: (03) 9888 6944

Recommended use of the chemical and restrictions on use Protection of fabric, sprayed on to surface.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Aspiration Hazard: Category 1 Carcinogenicity: Category 1 Flammable Liquids: Category 3 Germ Cell Mutagenicity: Category 1 Signal Word (s)

DANGER

Hazard Statement (s)

H226 Flammable liquid and vapour.H304 May be fatal if swallowed and enters airways.H340 May cause genetic defects.H350 May cause cancer.

Pictogram (s) Flame, Health hazard



Precautionary statement – PreventionP201 Obtain special instructions before use.P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting//equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use carbon dioxide, dry chemical, foam, water fog or water mist for extinction.

Precautionary statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

| Name | CAS | Proportion |
|--|------------|------------|
| Naphtha (petroleum), hydrotreated heavy | 64742-48-9 | >60-100 % |
| Stabiliser | | 0-<10 % |
| Ingredients determined not to be hazardous | | Balance |

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

First Aid Facilities

Eyewash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, dry chemical, foam, water fog or water mist.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including incomplete combustion products, carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

•3Y

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material, however, the TWA exposure standards for refined mineral oil mist is 5 mg/m³. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

Biological Limit Values

No biological limits allocated.

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as nitrile rubber. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

| Properties | Description | Properties | Description |
|--|----------------------------|---------------------------|-------------------------------------|
| Form | Liquid | Appearance | Water-white liquid |
| Colour | Water-white | Odour | Mild petroleum |
| Decomposition Temperature | Not available | Melting Point | Not available |
| Boiling Point | 156 - 174°C | Solubility in Water | Not available |
| Specific Gravity | 0.75 | рН | Not available |
| Vapour Pressure | 1.9 kPa (38°C) | Vapour Density (Air=1) | 5.0 |
| Evaporation Rate | 0.28 (N-Butyl Acetate = 1) | Odour Threshold | Not available |
| Viscosity | Not available | Volatile Component | 100% |
| Partition Coefficient: n- octanol/water | Not available | Flash Point | 41°C (Pensky Martens Closed cup) |
| Flammability | Flammable | Auto-Ignition Temperature | 293°C |
| Flammable Limits - Lower | 0.8% | Flammable Limits - Upper | 7.0% |

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of storage and handling.

Reactivity and Stability

Reacts with incompatible materials

Conditions to Avoid

Heat, open flames and other sources of ignition

Incompatible materials

Strong oxidants like liquid chlorine, concentrated oxygen, sodium hypochlorite.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

Possibility of hazardous reactions

Not available

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen. Mineral oils, untreated or mildly treated is listed as a Group 1: Carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential Not available

Other Adverse Effects Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers.

14. TRANSPORT INFORMATION

Transport Information

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail.

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives

- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)

- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents
- Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3 UN No: 1993 Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (CONTAINS NAPHTHA (PETROLEUM) HYDROTREATED HEAVY) Packing Group: III EMS: F-E, S-E Special Provisions: 223, 274, 955

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Class/Division: 3 UN No: 1993 Proper Shipping Name: flammable liquid, n.o.s. (Contains Naphtha (petroleum), hydrotreated heavy) Packing Group: III Packaging Instructions (passenger & cargo): 355 Packaging Instructions (cargo only): 366 Hazard Label: Flammable Liquid Special Provisions: A3

U.N. Number

1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S.(Contains Naphtha (petroleum), hydrotreated heavy)

Transport hazard class(es) 3 Packing Group III Hazchem Code • 3Y Special Precautions for User Not available IERG Number 14 IMDG Marine pollutant No Transport in Bulk Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

S5

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS reviewed: December 2016 Supersedes: January 2011

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of classification and labelling of chemicals.

Contact Person/Point

DISCLAIMER: The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.