

Material Safety Data Sheet

CS: 1.4.22

Page: 1 of 5

Infosafe No™ SILAC Issue Date : July 2008 ISSUED by MING CS: 1.4.22

Product Name : **MING 3000B**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name MING 3000B
Product Code 8145500
Company Name MING STEALSTOPPER (VIC) PTY LTD
Address 275 Canterbury Road Canterbury
Victoria 3126 Australia
Telephone/Fax Number Tel: (03) 9888-6789
Fax: (03) 9888-6944
Recommended Use Under Body Rust Preventive.
Other Names Name Product Code
Paint

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

Risk Phrase(s) R10 Flammable.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

Safety Phrase(s) S16 Keep away from sources of ignition - No smoking.
S2 Keep out of reach of children.
S23(2) Do not breathe vapour.
S23(3) Do not breathe spray.
S24/25 Avoid contact with skin and eyes.
S37/39 Wear suitable gloves and eye/face protection.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.
S9 Keep container in a well ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Liquid Hydrocarbons	64742-88-7	10-<30 %
	Corrosion inhibitor		10-<30 %
	Inert Pigment		10-<30 %
	Waxes		10-<30 %

4. FIRST AID MEASURES

Inhalation Remove the source of contamination or move the affected person to fresh air. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion Do NOT induce vomiting. Wash out mouth with water. Seek medical attention.

Skin Wash affected area thoroughly with copious amounts of running water. Remove contaminated clothing and wash before reuse. If symptoms develop seek medical attention.

Eye If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.

First Aid Facilities Eye wash and normal washroom facilities.

Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Material Safety Data Sheet

CS: 1.4.22

Page: 2 of 5

Infosafe No™ SILAC	Issue Date : July 2008	ISSUED by MING	CS: 1.4.22
--------------------	------------------------	----------------	------------

Product Name : **MING 3000B**

Suitable Extinguishing Media	Use of foam or dry chemical.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Specific Hazards	Flammable liquid. May react or explode violently under fire conditions.
Hazchem Code	3[Y]
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Avoid accidents, clean up immediately. Wear protective clothing to minimise skin and eye exposure. Evacuate all unprotected personnel. Remove all sources of ignition. Increase ventilation. If possible contain the spill, prevent run-off into drains and waterways. Place inert, non-combustible absorbent material onto spillage. Collect using clean, non-sparking tools and place into suitable labelled containers. Dispose of the material in accordance with applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.
-----------------------------	--

7. HANDLING AND STORAGE

Precautions for Safe Handling	Wear appropriate protective clothing and equipment to prevent inhalation, skin and eye contact. Use in designated areas with adequate ventilation. Prevent the creation of vapour or mist in the work atmosphere. Do not use near welding or other ignition sources and avoid sparks. Practice good personal hygiene, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities. When using do not eat, drink or smoke. Keep containers closed when not in use.
Conditions for Safe Storage	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.
Corrosiveness	Not considered corrosive to metals.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m ³ . As with all chemicals, exposure should be kept to the lowest possible levels.
Biological Limit Values	TWA - the Time-Weighted Average airborne concentration over an eight-hour working day, for a five-day working week. No biological limit allocated.
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Material Safety Data Sheet

CS: 1.4.22

Page: 3 of 5

Infosafe No™ SILAC	Issue Date : July 2008	ISSUED by MING	CS: 1.4.22
--------------------	------------------------	----------------	------------

Product Name : **MING 3000B**

Eye Protection	Safety glasses with side shields or face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances ie. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform to Australian/New Zealand Standard AS/NZS 1337- Eye Protectors for Industrial Applications.
Hand Protection	Impervious gloves recommended such as laminated film or nitrile. Final choice of appropriate gloves will vary according to individual circumstances ie. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161 Occupational protective gloves- Selection, use and maintenance.
Body Protection	Suitable work wear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Near black viscous fluid.
Odour	Solvent odour
Melting Point	Not available
Boiling Point	145-360°C
Solubility in Water	Insoluble
Specific Gravity	1.03
pH Value	Not applicable
Vapour Pressure	Not available
Vapour Density (Air=1)	Not available
Flash Point	23-61°C
Flammability	Flammable liquid
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions of storage and handling.
Incompatible Materials	Strong oxidising agents.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No toxicity data are available for this product.
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Harmful: may cause lung damage if swallowed. May cause irritation of the gastrointestinal system.
Skin	May cause skin irritation which may result in redness and itchiness. Prolonged contact may cause defatting and drying of the skin.
Eye	May be irritating to eyes, which may cause tearing, stinging and redness.

Material Safety Data Sheet

CS: 1.4.22

Page: 4 of 5

Infosafe No™ SILAC Issue Date : July 2008 ISSUED by MING CS: 1.4.22

Product Name : **MING 3000B**

12. ECOLOGICAL INFORMATION

Ecological Information Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Ecotoxicity Not available

Persistence / Degradability Not available

Mobility Not available

Bioaccumulative Potential Not available

Environ. Protection Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information This material is classified as a Class 3 (Flammable Liquid) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 3 (Flammable Liquid) are incompatible in a placard load with any of the following:

- Class 1, Explosive
- Class 2.1, Flammable Gas, if both the Class 3 and Class 2.1 dangerous goods are in bulk
- Class 2.3, Toxic Gas
- Class 4.2, Spontaneously Combustible Substance
- Class 5.1, Oxidising Agent
- Class 5.2, Organic Peroxide
- Class 6, Toxic and Infectious Substances, if the Class 3 dangerous goods are nitromethane.
- Class 7, Radioactive Substance

U.N. Number 1263

Proper Shipping Name PAINT

DG Class 3

Hazchem Code 3[Y]

Packaging Method 3.8.3RT1

Packing Group III

EPG Number 3C1

IERG Number 14

15. REGULATORY INFORMATION

Regulatory Information Classified as Hazardous according to criteria of the National Occupational Health & Safety Commission (NOHSC) Australia. Classified as a Scheduled Poison S5 according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

Poisons Schedule S5

Hazard Category Harmful, Dangerous for the environment

16. OTHER INFORMATION

Date of preparation or last revision of MSDS MSDS Review: July 2008
Supersedes: January 2003

Contact Person/Point DISCLAIMER: The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user

Material Safety Data Sheet

CS: 1.4.22

Page: 5 of 5

Infosafe No™ SILAC	Issue Date :July 2008	ISSUED by MING	CS: 1.4.22
--------------------	-----------------------	----------------	------------

Product Name : **MING 3000B**

is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.
...End Of MSDS...

© Copyright ACOHS Pty Ltd
Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.
Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed on this site is the intellectual property of Acohs Pty Ltd.
Copying of any MSDS displayed on this site is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed on this site cannot be