

# Material Safety Data Sheet

Page 1 of 3

Infosafe No. **SILAG** Issue Date : January 2003 ISSUED by MING

Product Name : **MING SOUND DEADENER**

Classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** MING STEALSTOPPER (VIC) PTY LTD  
**Address** 275 Canterbury Road Canterbury  
Victoria 3126 Australia  
**Tel/Fax** Tel: (03) 9888-6789 Fax: (03) 9888-6944

## IDENTIFICATION

**Product Name** MING SOUND DEADENER  
**Other Names** Name Product Code  
Paint  
Flammable Liquid  
HFP  
Immiscible with water  
**UN Number** 1263  
**Poisons Schedule** S5  
**Product Use** Under Body Rust Preventive.

## Physical Data

**Appearance** Dark brown viscous fluid with solvent odour.  
**Boiling Point** 145-360°C  
**Vapour Pressure** Not Available.  
**Specific Gravity** 1.03  
**Flash Point** 23-61°C  
**Flamm. Limit LEL** Not Available.  
**Flamm. Limit UEL** Not Available.  
**Solubility in Water** Insoluble.

## Other Properties

**Volatile Component** 47%

## Ingredients

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>
	Liquid hydrocarbons	64742-68-7	30-60 %
	Corrosion Inhibitor		10-30 %
	Waxes		10-30 %
	Inert Pigment		10-30 %
	Colouring		0-9.99 %
	thickener		0-9.99 %

**Information on Composition** (All hazardous substances as defined in Appendix 5 of the NOHSC Guidance Note for completion of a Material Safety Data Sheet, February 1990, are listed by chemical name and CAS No. Other commercially confidential components are by generic name).

**Other Information** \*\* Liquid Hydrocarbons as defined in Schedule 5 of Poisons Regulations (Boiling range 145 - 360°C).

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Swallowed** Irritating and nauseating.  
**Acute - Eye** Irritating.  
**Acute - Skin** Mildly irritating on prolonged contact by defatting skin.  
**Acute - Inhaled** May cause dizziness or headache on prolonged exposure.

# Material Safety Data Sheet

Page 2 of 3

Infosafe No. SILAG Issue Date : January 2003 ISSUED by MING

Product Name : **MING SOUND DEADENER**

Classified as hazardous according to criteria of NOHSC

**Chronic** Prolonged contact may cause skin irritation. Apply a protective layer by regular use of a barrier cream, minimises such irritation.

## First Aid

**Swallowed** Contact a doctor or Poisons Information Centre. DO NOT induce vomiting. Give a glass of water. Repeat if vomiting occurs. If the patient is not fully conscious do not give anything by mouth.

**Eye** Remove contact lenses if worn and wash eyes with water.

**Skin** Remove contaminated clothing and wash skin with water then with soap and water.

**Inhaled** Remove from contaminated area. Apply artificial respiration if not breathing.

## Advice to Doctor

**Advice to Doctor** If swallowed, treat for liquid hydrocarbons like kerosene.

## Other Health Hazard Information

## PRECAUTIONS FOR USE

**Exposure Limits** TLV-TWA for these liquid hydrocarbons is 100 PPM.

**Other Exposure Info.** The Threshold Limit Value-Time Weighted Average (TLV-TWA) is the time-weighted average concentration for a normal 8-hour week day and a 40 hour week, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.

**Eng. Controls** Application by spray will normally require mechanical ventilation to maintain the concentration below the TLV.

## Personal Protection

**Protective Equip.** Keep out of the eyes and mouth. Avoid prolonged contact with the skin and prolonged breathing its vapour.

## Flammability

**Fire Hazards** Flammable. Flash point between 23 and 61°C.

## SAFE HANDLING INFORMATION

## Storage and Transport

**Storage and Transport** Dangerous Goods Class 3 - must be stored and transported in accordance with State or Territory dangerous goods regulations.

**IERG Number** 14

## Spills and Disposal

**Spills & Disposal** Absorb on vermiculite or similar absorbing material and collect in drums.

## Fire/Explosion Hazard

**Fire/Explos. Hazard** Danger of violent reaction or explosion. Wear breathing apparatus and protective gloves for fire only. Contain. Prevent by any means available spillage from entering drains or water course.

**Extinguishing Media** Use foam or dry agent.

## OTHER INFORMATION

## CONTACT POINT

**Contact** DISCLAIMER: The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.

# Material Safety Data Sheet

Page: 3 of 3

Infosafe No.	SILAG	Issue Date : January 2003	ISSUED by MING
--------------	-------	---------------------------	----------------

Product Name : **MING SOUND DEADENER**

Classified as hazardous according to criteria of NOHSC

---

...End Of MSDS...