

# Material Safety Data Sheet

Page: 1 of 3

Product Name : MING PAINT PROTECTION - NZ

Classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** Ming Stealstopper (VIC) Pty Ltd  
**Address** 275 Canterbury Road Canterbury  
Victoria 3126 Australia  
**Tel/Fax** Tel: (03) 9888-6789 Fax: (03) 9888-6944

## IDENTIFICATION

**Product Name** MING PAINT PROTECTION - NZ  
**Proper Shipping Name** PAINT  
**UN Number** 1263  
**DG Class** 3  
**Packing Group** III  
**Hazchem Code** 3[Y]  
**Poisons Schedule** Not Scheduled  
**Product Use** Automotive paint polish  
**Synonyms** Paints

## Physical Data

**Appearance** Viscous grey brown opaque cream  
**Melting Point** 150 - 200°C  
**Boiling Point** 150 - 200°C  
**Vapour Pressure** Not applicable  
**Specific Gravity** 0.90 @ 20°C  
**Flash Point** 40°C

## Other Properties

**Volatile Component** Organic solvents  
Volatiles (%) Not applicable  
**Autoignition Temp.** Not applicable  
**pH Value** Not applicable

## Ingredients

| Ingredients | Name          | CAS       | Proportion |
|-------------|---------------|-----------|------------|
|             | White Spirits | 8030-30-6 | 10-30 %    |

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Swallowed** Moderately toxic. May be harmful if swallowed  
**Acute - Eye** A moderate eye irritant  
**Acute - Skin** Contact with skin may result in irritation  
**Acute - Inhaled** Inhalation may be harmful. May cause headaches, weakness and dizziness. May cause irritation to the mouth, nose, throat, lungs, mucous membranes and respiratory tract.  
**Chronic** Knowledge is based on that of the constituents. Repeated or prolonged skin contact may cause sensitisation, irritation and dermatitis.

## First Aid

**Swallowed** Rinse mouth thoroughly with water immediately. DO NOT induce vomiting because of risk of aspiration or it may cause further damage to the throat. Seek medical advice if effects persist.

# Material Safety Data Sheet

Page: 2 of 3

Product Name : MING PAINT PROTECTION - NZ

Classified as hazardous according to criteria of NOHSC

|                |  |
|----------------|--|
| <b>Eye</b>     | Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. If irritation occurs, seek medical advice. Remove contact lenses if worn.                                |
| <b>Skin</b>    | Wash with plenty of soap and water. If swelling, redness, blistering or irritation occurs, seek medical advice. Apply lanolin rich cream to affected areas. Remove contaminated clothes and wash before reuse. |
| <b>Inhaled</b> | Remove victim to fresh air. Recovery should be rapid after removal from exposure   |

## Advice to Doctor

**Advice to Doctor** Consult Poisons Information Centre and treat the patient symptomatically

## Other Health Hazard Information

## PRECAUTIONS FOR USE

|                        |  |
|------------------------|--|
| <b>Exposure Limits</b> | TLV as Diatomaceous Earth (Amorphous Silicon Dioxide) is 10 mg/m <sup>3</sup> (NONSC 1990)<br>TLV (as White Spirit) is ppm 100 - 5/5 mg/m <sup>3</sup> (NONSC 1990). ILV is the time weighted average concentration of the work atmosphere over a normal 8 hour work day and a 40 hour work week. Nearly all workers may be repeatedly exposed to this level, day after day, without adverse effect. |
| <b>Eng. Controls</b>   | Since this product is used on exterior surfaces, no special ventilation requirements are necessary.  |

## Personal Protection

|                          |  |
|--------------------------|--|
| <b>Protective Equip.</b> | It is advisable to wear the following protective equipment:<br>Overalls, safety glasses, gloves and footwear. The use of barrier cream may be beneficial. Avoid skin and eye contact and inhaling the vapour. Wash contaminated clothing and protective equipment before storing or reusing. Avoid carrying contaminated rags in pockets or wearing soaked clothing. Showering at the end of the working day is recommended. Always wash hands before smoking, eating, drinking or using the toilet. |
|--------------------------|--|

## Flammability

**Fire Hazards** Flammable liquid. Avoid all ignition sources, heat, sparks and naked flames

## SAFE HANDLING INFORMATION

### Storage and Transport

|                             |  |
|-----------------------------|--|
| <b>Transport</b>            | When transporting Class 3 (Flammable Liquids), DO NOT load on the same vehicle with the following classes:<br>1, 2.1, 2.3, 4.2, 5.1, 5.2 and 7<br>Packaging and labelling:<br>Ensure all containers are clearly labelled, airtight, strong and rigid and held in an upright position. The current packaging is 500 ml in rigid PVC container |
| <b>Proper Shipping Name</b> | PAINT  |
| <b>EPG Number</b>           | 3C1  |
| <b>IERG Number</b>          | 14   |
| <b>Packaging Method</b>     | 5.9.3RT1   |
| <b>Handling and Storage</b> | Storage and transport:<br>Dangerous goods information: Hazchem 3Y, Class 3.2 packaging group 111. Store in a cool, dry, well ventilated area away from all sources of heat.  |

## Spills and Disposal

# Material Safety Data Sheet

Page: 3 of 3

Product Name : MING PAINT PROTECTION - NZ

Classified as hazardous according to criteria of NOHSC

**Spills & Disposal** Remove all sources of heat and ignition. Use absorbent sand or cloth to soak up spillage, but not sawdust. Collect and seal properly labelled drums for disposal. Dampen all rags and cloths prior to disposal. Do not incinerate empty containers. Empty containers must be decontaminated and destroyed. Wash residues away with detergent and excess water. DO NOT smoke during clean up procedures. For large spills, and if there is a danger of ignition or contamination of sewerage and waterways, contact the Fire Brigade or the Local Authorities. Non biodegradable. Avoid contaminating waterways. This product may be hazardous to the environment.

## Fire/Explosion Hazard

**Hazchem Code** 3[Y]

## OTHER INFORMATION

**Risk Statement** R45(2) May cause cancer.  
R65 Harmful: may cause lung damage if swallowed.

**Safety Statement** S23 Do not breathe gas/fumes/vapour/spray  
S24/25 Avoid contact with skin and eyes.  
S37/39 Wear suitable gloves and eye/face protection.  
S38 If insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if unwell, contact a doctor or Poisons Information Centre immediately (show the label where possible).  
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**Hazard Category** Toxic

## CONTACT POINT

**Contact** DISCLAIMER: The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.  
...End Of MSDS...