

# MATERIAL SAFETY DATA SHEET

Ref:TRUGUARD\_LOWER\_MSDS.doc Page 1 of 3

# SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT (MATERIAL) NAME Truguard Lower

OTHER NAMES

RECOMMENDED USE Automotive soundproofing coating for application to underside of vehicle.

SUPPLIER NAME/ADDRESS Truseal Car Care 210 Canterbury Road, Canterbury VIC 3126 Australia

TELEPHONE 1300 330 822

## SECTION 2 HAZARDS IDENTIFICATION

HAZARD Classified as hazardous according to criteria of NOHSC Australia.

CLASSIFICATION Not classified as dangerous according to criteria of Australian Dangerous Goods Code.

Harmful

RISK PHRASE(S) R36: Irritating to eyes. R65: Harmful: May cause lung damage if swallowed.

SAFETY PHRASE(S) S2: Keep out of reach of children. S23: Do not breathe fumes/vapour. S24: Avoid contact with skin.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

#### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

MIXTURE

Chemical identity of ingredients Proportion of ingredients CAS Number(s) for ingredients

Balance of formulation consists of other ingredients determined not to be hazardous.

#### SECTION 4 FIRST AID MEASURES

SWALLOWED If poisoning occurs, contact a doctor or Poisons Information Centre 131 126. If swallowed, do NOT

induce vomiting. Give glass of water. Thoroughly rinse mouth with water.

EYE Immediately flush eyes with plenty of running water for at least 15 minutes. Ensure that under the

eyelids are flushed also. Seek medical attention.

SKIN Remove contaminated clothing and wash before reuse. Wash off skin with soap and water.

Seek medical assistance if irritation persists.

INHALATION Remove victim from exposure, keep warm and at rest. Medical attention or special treatment required.

ADVICE TO DOCTOR Treat symptomatically

### SECTION 5 FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA Foam, Carbon Dioxide, Dry Chemical Powder and Water Fog

HAZARDS FROM COMBUSTION PRODUCTS Combustion will release toxic gasses (COx)

SPECIAL PROTECTIVE PRECAUTIONS Fire fighters to wear self-contained breathing apparatus if risk of exposure to vapour or

products of decomposition (COx) evolved

ADDITIONAL INFORMATION Not classed as flammable under the Australian Code for transport of dangerous goods.

HAZCHEM CODE Not applicable

# SECTION 6 ACCIDENTAL RELEASE MEASURES

METHODS AND MATERIALS FOR

EMERGENCY PROCEDURES Extinguish any source of flame, evacuate area, clearing all unnecessary personnel. Contain liquid

with soil/sand. Prevent liquid from entering storm water drains, basements or workpits.

Wear Protective goggles to prevent eye contamination.

Absorb spill with soil/sand and recover material into mild steel drums. Label drums correctly.

Refer to State Land Waste Management Authority. Empty containers must be decontaminated.

CONTAINMENT AND CLEAN UP Normally suitable for disposal at approved and waste site.

#### truseal car care

#### SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING Wear protective goggles and rubber gloves to prevent eye and skin contamination.

CONDITIONS FOR SAFE STORAGE Keep containers tightly sealed when not in use. Store in a well ventilated area and out of direct

sunlight. Check area regularly for spills.

INCOMPATIBILITIES Not to be loaded with dangerous when wet substances (Class 4.3), oxidising agents (Class 5),

cyanides (Class 6), strong acids (Class 8).

#### SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL EXPOSURE STANDARDS Not established for the product. However all references regarding liquid hydrocarbons refer

specifically to Occupational Exposure Limit of 100ppm TWA.

BIOLOGICAL LIMIT VALUES

ENGINEERING CONTROLS

PERSONAL PROTECTION Avoid unnecessary contact as good work practice. Wash contaminated clothing and protective

equipment before storing and re-use. Wash hands before eating, smoking or using the toilet.

RESPIRATORY PROTECTION It is usually safe not to use respiratory protection. However, there may be circumstances where

use of a mask or other device is appropriate. Use judgement.

For assistance in selecting suitable equipment consult AS/NZ1715.

EYE PROTECTION Eye protective measures are normally necessary, and are suggested when using this product.

Consult AS1336 and AS/NZ1715.

PROTECTIVE GLOVES Rubber, PVC or other protective gloves are necessary and desirable, especially if a product is being used

frequently or for lengthy periods. Consult AS2161 for guidance.

PROTECTIVE CLOTHING Clean overalls should be worn, preferably with an apron. Consult AS2919 for clothing guidance.

SAFETY FOOTWEAR Wearing safety boots is advisory. Consult AS/NZ2210 for advice on Occupational Protective Footwear.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Dark brown-black opaque, fluid

ODOUR Mild characteristic odour
FLAMMABILITY Product is not flammable

MELTING POINT 0°C

BOILING POINT 100°C

FLASH POINT Unknown

VAPOUR PRESSURE 10mm Hg @ 23°C

VOLATILES 40%

VAPOUR DENSITY Unknown

FLAMMABILITY LIMITS Unknown

SPECIFIC GRAVITY 1.24

pH 8.5 - 10

SOLUBILITY IN WATER Miscible only in bulk - once film fully dry insoluble

AUTOIGNITION TEMPERATURE Unknown

# SECTION 10 STABILITY AND REACTIVITY

CHEMICAL STABILITY Stable

CONDITIONS TO AVOID Do not mix with oxidising agents (Class 5).

INCOMPATIBLE MATERIALS Not to be loaded with dangerous when wet substances (Class 4.3), oxidising agents (Class 5),

cyanides (Class 6), strong acids (Class 8) or food stuffs.

HAZARDOUS DECOMPOSITION PRODUCTS Upon combustion oxides of carbon. (CO, COx)

HAZARDOUS REACTIONS Oxidising agents (Class 5).

## SECTION 11 TOXICOLOGICAL INFORMATION

LIQUID HYDROCARBONS Oral Toxicity (Rats): LD>50 5 g/kg Slightly toxic (estimated) based on testing of similar products and/or

the components. Dermal Toxicity (Rabbits):  $LD_{50} > 2 g/Kg$ .

SYMPTOMS OF EXPOSURE

SWALLOWED Practically non-harmful. However, ingestion of large amounts may result in irritation to the gastro-intestinal tract.

EYE Mild irritation

SKIN Mildly irritating to the skin. However, repeated or prolonged contact may result in irritation or

dermatitis in some individuals.

INHALATION Prolonged exposure may cause somnolence (sleep inducing) and narcosis. The dust (dry) is harmful and

irritating to the upper respiratory tract. Can present as a hazard over repeated exposures over long periods.

ACUTE

DELAYED

Additional Information

Aggravated medical conditions

caused by exposure

# SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY
PERSISTANCE AND DEGRADABILITY

Product is not biodegradable, although surfactants used are biodegradable.

MOBILITY Once dry film is not mobile

Additional Information

Environmental Fate (Exposure) Bioaccumulative potential

#### SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS AND CONTAINERS: Refer to State Land Waste Management Authority. Empty containers must be decontaminated.

Normally suitable for disposal at approved land waste site.

SPECIAL PRECAUTIONS FOR LANDFILL OR INCINERATION

# SECTION 14 TRANSPORT INFORMATION

UN NUMBER Not applicable
UN PROPER SHIPPING NAME Not applicable
CLASS AND SUBSIDIARY RISK Not applicable
PACKING GROUP Not applicable
SPECIAL PRECAUTIONS FOR USED Not applicable
HAZCHEM CODE Not applicable

# SECTION 15 REGULATORY INFORMATION

POISON SCHEDULE Unscheduled

OHS Not considered a hazard

ENVIRONMENTAL Not considered a hazard

Additional Information

Additional national and/or international

regulatory information

# SECTION 16 OTHER INFORMATION

DATE OF PREPARATION OR LAST

REVISION OF THE MSDS 19 December 2011

PREPARED BY Glen Bowring B App Sc (App Chem)

Additional Information

Key/Legend to abbreviations and acronyms used in the MSDS Literature references

Sources for data. Material Safety Data Sheets from Suppliers

List of Designated Substances - Worksafe Australia (on-line)

Australian Dangerous Goods Code 6th Edition

Standard for the Uniform Scheduling of Drugs and Poisons No 21

### DISCLAIMER

This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Truseal Pty Ltd.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

Truseal Pty Ltd however makes no warranty whatsoever, expressed, implied or of merchantability regarding the accuracy of such data or the results to be obtained from the use thereof and assumes no responsibility for injury to buyer or third persons or for any damage to property, Buyer assumes all risks.