Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 1 of Total 8

SECTION 1 – STATEMENT OF CHEMICAL PRODUCT AND COMPANY IDENTIFICATION				
SUPPLIER:	MotorOne Group Pty Ltd			
ADDRESS:	Level 9, 3 Nexus Court, Mulgrave, 31	Level 9, 3 Nexus Court, Mulgrave, 3170 VIC		
Trade Name:	HYDRO G9+ SURFACE COATING – 50mL			
TELEPHONE:	03 8809 2700	FAX:	03 9888 6944	
AH EMERGENCY TELEPHONE:	0411126474 in Australia	Synonym:	NA	
Substance:	Solvant based coating	Product Use:	Industrial surface coating	
Creation Date:	April 2023	Revision Date:	April 2028	

SECTION 2 – HAZARDS IDENTIFIC	ATION	
Classification of the substance of	or mixture	
Dangerous Goods	Classified as <b>LIMITED QUANTITY DANGEROUS GOODS</b> by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".	
GHS Classification	Acute Toxicity - Inhalation: Category 4	
	Aspiration Hazard: Category 1	
	Eye Irritation: Category 2A	
	Flammable Liquids: Category 2	
	Skin Irritation: Category 2	
Poisons Schedule	S6	
abel elements		
GHS label pictograms		
Signal word	DANGER	
Hazard statement(s)		
H225	Highly flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
Precautionary statement(s): Ge		
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
Precautionary statement(s): Pre		
P210	Keep away from heat and sparks - No smoking.	
P233	Keep container tightly closed.	
P240	Ground container and receiving equipment.	
P241 P242	Use explosion-proof electrical equipment.	
P242 P243	Use only non-sparking tools.	
P243 P261	Take precautionary measures against static discharge.  Avoid breathing dust, vapours and spray.	
P264	Wash contaminated skin thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves, protective clothing and eye protection.	
1 200	Trea. protective gloves, protective dotting and eye protection.	

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 2 of Total 8

Precautionary statement(s): Response			
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.		
P331	Do NOT induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.		
P332+P313	If skin irritation occurs: Get medical advice.		
P362	Take off contaminated clothing and wash before reuse.		
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for		
	breathing.		
P312	Call a POISON CENTER or doctor if you feel unwell.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if		
	present and easy to do. Continue rinsing.		
P337+P313	If eye irritation persists: Get medical advice.		
P370+P378	In case of fire: Use alcohol resistant foam, water spray or fog, carbon dioxide, dry chemical		
	powder for extinction.		
Precautionary statement(s): Sto	orage		
P405	Store locked up.		
P403+P235	Store in a well-ventilated place. Keep cool.		
Precautionary statement(s): Dis	Precautionary statement(s): Disposal		
P501	Dispose of contents and container in accordance with local regulations.		
Note			
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its concentrated form, as supplied.		

Ingredients:	CAS Number:	Proportion (%w/w):
Ligroine	8032-32-4	< 40
2-Butoxyethanol	111-76-2	< 20
Silica crystalline - quartz	14808-60-7	< 15
Silicon Carbide	409-21-2	< 10
Ingredients determined to be non-		
hazardous at the concentrations used	various	balance
(including water)		

SECTION 4 – FIRST AID M	EASURES
Inhalation	Remove person to fresh air away from exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Obtain medical attention if symptoms occur.
Skin contact	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
Ingestion	Do NOT induce vomiting. Do NOT attempt to give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek immediate medical advice (e.g. doctor).
Advice to Doctor	Treat symptomatically.
First Aid Facilities	Eye wash station. Normal washroom facilities.

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 3 of Total 8

SECTION 5 – FIRE FIGHTING	MEASURES
Fire and Explosion Hazards	Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.  Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including oxides of nitrogen, hydrogen fluoride, hydrogen chloride, carbon monoxide and carbon dioxide.
Extinguishing Media	Alcohol resistant foam, water spray or fog, carbon dioxide, dry chemical powder. Do not use water jet.
Fire Fighting	Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses
Flash Point	>20°C
Hazchem	• 3YE

#### **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**Emergency Procedures** 

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible, contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place it into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

SECTION 7 – HANDLING AN	ID STORAGE
Handling	Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well- ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities
Storage	Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 4 of Total 8

SECTION 8 - EXPOSURE CO	NTROLS AND PERSONAL PROTECTION
Exposure Limits	National Occupational Exposure Limits, as published by Safe Work Australia:
Exposure Limits	Time-weighted Average (TWA):
	None established for product.
	For ingredients:
	• 2-Butoxyethanol: 20ppm, 96.9 mg/m <sup>3</sup>
	• Quartz: 0.05 mg/m³ (note: Carc 1A)
	• Silicon Carbide 10 mg/m <sup>3</sup>
	Short Term Exposure Limit (STEL):
	None established for product.
	For ingredients:
	• 2-Butoxyethanol: 50ppm, 242 mg/m <sup>3</sup>
	TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight- hour working day, for a five-day week.
	STEL(Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.
	'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.
	Carc.lA: Known to have carcinogenic potential for humans.
Ventilation	This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.
	Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NI5 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.
Personal Protective	Use good occupational work practice. The use of protective clothing and equipment depends upon
Equipment	the degree and nature of exposure. The following protective equipment should be available;
Eye Protection	Safety glasses, chemical goggles or face shield should be used for handling concentrate in quantity, cleaning up spills, decanting, etc. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective workwear, e.g. rubber or plastic apron, sleeves, boots and cotton overalls
	buttoned at neck and wrist are recommended. Chemical resistant apron is recommended where large quantities are handled.
Respirator	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 5 of Total 8

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Non-viscous liquid	Colour	Not available
Odour	Solvent	Specific Gravity	0.75 – 0.90 @ 25 °C
<b>Boiling Point</b>	Not available	Freezing Point	Not available
Vapour Pressure	Not available	Vapour Density	Not available
Flash Point	>21°C	Flammable Limits	none
Water Solubility	Insoluble	рН	Not applicable

SECTION 10 – STABILITY AND REACTIVITY		
Reactivity	Stable at normal temperatures and pressure. Reacts with strong oxidizing agents.	
Conditions to Avoid	Heat, open flames, direct sunlight, and other sources of ignition.	
Incompatibilities	Strong oxidizing agents.	
Hazardous	Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases	
Decomposition	including hydrogen fluoride, hydrogen chloride, chloride, carbon dioxide and carbon monoxide.	

SECTION 11 – TOXICOLOGI	CAL INFORMATION	
POTENTIAL HEALTH EFFECT	TS .	
No adverse health effects e	xpected if the product is handled in accordance with this Safety Data Sheet and the product label.	
	nay arise if the product is mishandled and overexposure occurs are:	
Inhalation	Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and	
	respiratory system.	
Skin contact	Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure	
	may cause skin dryness and cracking and may lead to dermatitis.	
Eye contact	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred	
	vision, and redness	
Ingestion	May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the	
	respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may	
	lead to death. May cause irritation to the mouth, throat, oesophagus and stomach with symptoms	
	of nausea, abdominal discomfort, vomiting and diarrhoea.	
Chronic exposure	No information available.	
Toxicology Information	Not toxic, based on ingredient calculated values.	
Carcinogen Status		
IARC	Not considered to be a carcinogenic hazard.	
	2-Butoxyethanol is listed as a Group 3: Not classifiable as carcinogenic to humans according to	
	International Agency for Research on Cancer (IARC).	
	Silicon Carbide is listed as a Group 2A: Probably carcinogenic to humans according to	
	International Agency for Research on Cancer (IARC).	
	This product contains crystalline silica. No exposure to free respirable crystalline silica is	
	anticipated during normal use of this product as silica is bound in the liquid/paste. It should be	
	noted, however, that respirable crystalline silica has been listed as a Group 1 human carcinogen	
	by the IARC. Inhalation of respirable silica may cause cancer, silicosis or other serious delayed	
	lung injury. Grinding or machining of coated materials may release silica. Use approved dust	
	respirator when grinding, sanding or machining the dried items.	
Respiratory Sensitisation	Not expected to be a respiratory sensitizer.	
Skin Sensitisation	Not expected to be a skin sensitizer.	
Germ cell mutagenicity	Not considered to be a mutagenic hazard.	
Reproductive Toxicity	Not considered to be toxic to reproduction.	
STOT-single exposure	Not expected to cause toxicity to a specific target organ.	
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.	
Aspiration Hazard	Expected to be an aspiration hazard.	

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 6 of Total 8

SECTION 12 – ECOLOGICAL INFORMATION		
Eco-toxicity	No information	
Persistence and degradability	No information.	
Bio accumulative potential	No information.	
Mobility in soil	No information.	
Other adverse effects	Not available	
<b>Environmental Protection</b>	Do not discharge this material into waterways.	

#### **SECTION 13 – DISPOSAL CONSIDERATIONS**

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

#### **SECTION 14 – TRANSPORT INFORMATION**

**Land Transport (ADG)** Classified as **LIMITED QUANTITY DANGEROUS GOODS** by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".



	<b>▼</b>				
UN Number	1993				
Proper Shipping Name	Flammable liquids, N.O.S (Contains Ligroine) LIMITED QUANTITY				
Class	3				
HAZCHEM Code	•3YE				
Packing Group	II				
ERG	14				
Limited Quantity	1L				
Marine Pollutant	No				
Note	Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG) The legislation defines dangerous goods as being packed in limited quantities if:  (a) The goods are packed in accordance with Chapter 3.4 of the ADG Code; and  (b) The quantity of dangerous goods in each inner packaging or in each article does not exceed the quantity specified in, or referred to, in column 7a of the Dangerous Goods List for those goods.  General requirements applicable to all packaging used for dangerous goods packed in limited quantities: Dangerous goods transported in limited quantities must be packed in packages that meet the following criteria:  a) packaging must be designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods; and  b) all packaging must meet the provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8; and c) all packaging must meet the construction requirements of 6.1.4, 6.2.1.2 and 6.2.4; and d) for articles of Division 1.4, Compatibility Group S, packaging must also fully comply with the provisions of 4.1.5.  This product is packed in inner packaging of 50 ml(< 1 L). The outer packaging is less than 20 kg. This product can be transported as "limited quantity" once meet all general requirements stated above.				

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 7 of Total 8

Marine Transport (IMO/IMDG): Classified as LIMITED QUANTITY DANGEROUS GOODS by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN Number	1993			
<b>Proper Shipping Name</b>	Flammable liquids, N.O.S (Contains Ligroine) LIMITED QUANTITY			
Class	3			
HAZCHEM Code	•3YE			
Packing Group	II			
EMS	EMS :F-E, S-E			
Limited Quantity	1L			
Marine Pollutant	No			
Special Provision	274			

**Air Transport (ICAO/IATA):** Classified as **LIMITED QUANTITY DANGEROUS GOODS** by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN Number	1993		
<b>Proper Shipping Name</b>	Flammable liquids, N.O.S (Contains Ligroine) LIMITED QUANTITY		
Class	3		
HAZCHEM Code	•3YE		
Packing Group	II		
Packaging Instructions	353 (passenger & cargo). 364 (cargo only)		
Limited Quantity	1L		
Special Provision	A3		

SECTION 15 – REGULATORY INFORMATION			
<b>GHS Classification</b>	Classified as Hazardous according to the Globally Harmonised System of Classification and		
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.		
SUSMP	S6		
AICS	All ingredients present on AICS		

Issue Date	April 2023			
Version Number	V3 Updated format			
Abbreviations and	ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.			
icronyms	AICS: Australian Inventory of Chemical Substances.			
•	CAS Number: Chemical Abstracts Service Registry Number.			
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals			
	HAZCHEM: An emergency action code of numbers and letters which gives information to emergency			
	services.			
	HCIS: Hazardous Chemical Information System			
	SWA: Safe Work Australia.			
	SDS: Safety Data Sheet			
	STEL: Short Term Exposure Limit.			
	SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.			
	TWA: Time Weighted Average.			
	UN Number: United Nations Number.			

$\frown$	 _ <b></b>		EET	
	•	_ ^ ^	 	
- V - I				

Product Name: HYDRO G9+ SURFACE COATING – 50mL
Date of Issue: APR 2023 Page 8 of Total 8

Literature references	Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work Australia)	
	GHS Hazardous Chemical Information List (Safe Work Australia)	
	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.	
	Global Harmonized System of Classification and Labelling of Chemicals (GHS)	
	"Australian Exposure Standards". Safe Work Australia	
	Australian Code for The Transport of Dangerous Goods by Road and Rail	
	Standard for the Uniform Scheduling of Medicines and Poisons	
	Safety Data Sheets – individual raw materials – Suppliers	
	HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.	
Disclaimer	This SDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product, and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.	
End of SDS		